

AKG C451 B

REFERENCE SMALL-DIAPHRAGM CONDENSER MICROPHONE

GENERAL	Audio Frequency bandwidth	20 to 20000 Hz
	Sensitivity	9 mV/Pa
	Equivalent Noise Level	18 dB-A
	Signal to Noise	76 dB-A
	Preattunation Pad	-10; -20 dB
	Bass Cut Filter	75; 150 Hz
	Electrical Impedance	200 Ohms
	Recommended Load Impedance	1000 Ohms
	Audio Frequency bandwidth	20 to 20000 Hz
	Sensitivity	9 mV/Pa
	Equivalent Noise Level	18 dB-A
	Signal to Noise	76 dB-A
	Preattunation Pad	-10; -20 dB
	Bass Cut Filter	75; 150 Hz
	Electrical Impedance	200 Ohms
	Recommended Load Impedance	1000 Ohms

POLAR PATTERNS	Polar Pattern	cardioid
	Number	1
	Polar Pattern	cardioid
	Number	1

POWERING INTERFACE	Voltage	9 to 52 V
	Current	2 mA
	Voltage	9 to 52 V
	Current	2 mA

AUDIO OUTPUT

Type	Balanced XLR
Gender	Male
Contacts	3-pin
Type	Balanced XLR
Gender	Male
Contacts	3-pin

DESIGN

Finish	satın nickel plated
--------	---------------------

DIMENSIONS / WEIGHT

Net Weight	125 g
Height	160 mm
Diameter	19 mm
Net Weight	125 g
Height	160 mm
Diameter	19 mm
